

BOSS[®]
PRO**400**
COLORS

SIDING, WINDOW & METAL ROOF SEALANT

BOSS[®] 400 COLORS

Siding, Window & Metal Roof Sealant is a VOC Compliant, one-part, neutral curing, sealant formulated for the siding, window and metal roof market. It offers primerless adhesion to vinyl, wood, aluminum, brick, concrete, fiber cement and metal roofing. For use as a perimeter weatherseal for field glazing and window installation and as a primary backbedding compound. **BOSS[®] 400 COLORS** Siding, Window & Metal Roof Sealant cures in the presence of moisture to provide excellent resistance to cold, rain, ozone, heat and sunlight.

COLORS:**Cartridge**

400+ Colors Availability

FEATURES:

- BOSS[®] matches 40+ siding manufacturers colors
- Bonds to Kynar[®] 500*
- VOC compliant in all 50 states
- 50% movement
- Will not shrink
- Permanently flexible
- Minimum odor
- Available in 400+ colors
- 4 inch nozzle for hard to reach areas

*Kynar 500[®] is a trademark of Arkema Inc.

**Test small area for compatibility before painting

THE IDEAL SEALANT/ADHESIVE FOR:

- Vinyl
- Aluminum
- Wood
- Brick
- Concrete
- Fiber Cement
- Metal Roofing
- Field Glazing
- Window Installation
- Backbedding

PACKAGING:

- 10.1 oz. Cartridge

Scan the QR Code to see the full line of **BOSS^{PRO}** Products!



Visit Our Website

www.bossproducts.com

BOSS[®]
PRO**400**
COLORS

SIDING, WINDOW, & METAL ROOF SEALANT

TYPICAL PROPERTIES

Uncured

| | |
|--|---------------|
| Specific Gravity - White & Most colors | 1.18 |
| Specific Gravity - Clear | 1.03 |
| Sag/Slump | NIL |
| Tack-Free Time | 20 min. |
| Cure Time at 75°F (24°C) and 50% RH | 8.85 lb./gal. |
| (3/8" thickness) | 24 hours |
| Extrusion Rate | 250 g/min. |

Cured - Physical

| | |
|-----------------------------|----------------|
| Elongation | 550% |
| Durometer Hardness, Shore A | 25 points |
| Tensile Strength | 240 psi |
| VOC - White & Colors | 40 g/L |
| VOC - Clear | 38 g/L |
| Service Temperature | -40°F to 325°F |
| Application Temperature | -35°F to 140°F |

*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

LIMITATIONS

None

CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

Call The
BOSS[®]

800-928-BOSS

350 Ring Road • Elizabethtown • KY 42701
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412
www.bossproducts.com

SODAL
Soudal Accumetric