

**BOSS<sup>®</sup>**  
**PRO****RESISTS  
CRACKING****920****PREMIUM FLEX**

# ELASTOMERIC SEALANT PROFESSIONAL GRADE

**BOSS<sup>®</sup> 920**

is a mildew resistant and paintable elastomeric sealant formulated to provide long lasting, flexible, weatherproof seals between most common building materials including wood, masonry, concrete, brick, drywall, metal and glass. Its smooth, creamy consistency makes **BOSS<sup>®</sup> 920** easy to tool and cures to a tough flexible seal.

**COLORS:****Cartridge**

157525 - Clear

157526 - White

**FEATURES:**

- Interior or exterior
- 100% Flexible
- Exceptional flexibility
- Easy water clean up
- Mildew resistant
- Paintable in 2 hours
- ASTM C920, class 25
- Waterproof/weatherproof seal
- Low odor
- Permanent color
- UV resistant
- Non-yellowing
- Excellent adhesion on many materials

**THE IDEAL SEALANT/ADHESIVE FOR:**

- Building and Construction Joints
- Siding
- Window and Door Joints
- Sealing Corner Joints
- Sealing in Kitchens and Bathrooms
- Crown Molding
- Sealing Soffits and Eaves
- Sealing Around Baseboards and Trim
- Sealing Anywhere a Weathertight Seal is Desired

**PACKAGING:**

- 10.1 oz. Cartridge

Scan the QR Code to see the full line of **BOSS<sup>®</sup> PRO** Products!



Visit Our Website

[www.bossproducts.com](http://www.bossproducts.com)

**BOSS<sup>®</sup>**  
**PRO****RESISTS  
CRACKING****920**  
**PREMIUM FLEX**

# ELASTOMERIC SEALANT PROFESSIONAL GRADE

**TYPICAL PROPERTIES:**

% Non-Volatile, by weight (colors)	80.9%
% Non-Volatile, by weight (clear)	62%
% Volume Shrinkage: ASTM C-733-87	28%
Weight per gallon, approximate (colors)	12.2 lb./gal.
Weight per gallon, approximate (clear)	8.85 lb./gal.
pH	7.8 - 8.2
Tack-Free Time: ASTM D-2377-84	<25 minutes
Peel Strength: –Wood –Glass –Aluminum	26.0 pounds-force 29.0 pounds-force 32.0 pounds-force
ASTM C-731-87	17.2 grams/second
VOC (Colors)	13.7 grams/liter
VOC (Clear)	10.5 grams/liter
Service Temperature	-20°F to 185°F
Application Temperature	40°F to 110°F

\*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

**LIMITATIONS**

Not recommended for continuous water immersion or vehicular or foot traffic.

**CAUTION**

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

  
Soudal Accumetric

Call The  
**BOSS<sup>®</sup>**

**800-928-BOSS**

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)