

Extreme Weather Gun Grade Foam

TYPICAL PROPERTIES

| | |
|--------------------------------------|--------------------------------------|
| Density | 1.44 lbs./ft ³ |
| Insulation Factor R Value | 4.1 for 1 inch |
| Tack Free (1" bead) | 8 minutes (68°F & 65% RH) |
| Fully Cured (1" bead) | 12 hours (68°F & 65% RH) |
| Cuttable (1" bead) | 1 hour (68°F & 65% RH) |
| Tensile Strength | 4.35 psi |
| Shear Strength | 8.70 psi |
| Yield / 24 Oz. Can | up to 13 gallons freely foamed |
| Theoretical Yield 24 Oz. 1/4" bead | 4456 ft. |
| Theoretical Yield 24 Oz. 1/2" bead | 1114 ft. |
| Service Temperature | -40°F to 194°F |
| Application Temperature | -14°F to 120°F |
| | with a can temp between 41°F to 95°F |

DESCRIPTION

BOSS® 336 Extreme Weather Minimal Expanding Gun Foam is a top of the line one component, moisture curing polyurethane foam developed especially to perform under difficult freezing temperature conditions where traditional PU foams fail to extrude and cure. The foam will extrude at temperatures as low as -14°F and will cure at temperatures as low as -13°F with a can temperature of 41°F.

FEATURES

- AAMA 812-04 approved
- CFC propellant free
- Excellent adhesion on most substrates (except Teflon, PE and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post expansion)
- Very precise application due to the foam gun system

HOW TO USE

BOSS® 336 may be applied to all substrates except PE and PP. Apply to surfaces that are clean and free of dust and grease. Moistening of the surfaces improves adhesion, curing and denser cellular structure. **Shake can well before use**, attach foam gun and adjust screw. For best results, use in temperatures between 60°F and 100°F and at relative humidity of 40%. Clean with BOSS® 335 Gun and Foam Cleaner before curing.

SPECIFICATIONS

- ASTM E-2112
- ASTM E-283
- ASTM E-331
- ASTM E-547
- ASTM C-1620
- ASTM E-84 UL 723
- AAMA 812

CLEAN UP

Uncured sealant can be easily removed using BOSS® 335 or a solvent such as alcohol or acetone. For an environmental and health friendlier choice use BOSS® Biggie Wipes. If the sealant is cured it must be removed mechanically by cutting and scraping.

Continued...



APPLICATIONS

- Installing of window and doorframes
- Filling of cavities
- Sealing of all openings in roof construction
- Creation of a soundproof screen
- Mounting and sealing of window and doorframes
- Connecting of insulating materials and roof construction
- Application of a soundproofing layer on motors
- MANY MORE...

Scan the QR Code to see the full line of **BOSS®** Products!



SHIPPING LIMITATIONS

Ground shipments only. Cannot ship by air. | Reactive VOC 175 g/l (17.9% wt.)

CAUTION

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. Turn off all pilot lights, electrical igniters, burners and other sources of ignition or heat during use. Do not smoke, use matches or lighters while dispensing foam. Do not expose to direct sunlight, high heat or store in enclosed vehicle. Avoid breathing vapor/spray. Use only outdoors or in a well ventilated area with appropriate breathing apparatus. Avoid contact with skin and eyes. Wearing eyewear and gloves is recommended. Do not incinerate or puncture can. Store at temperatures below 120°F. **KEEP OUT OF REACH OF CHILDREN.** For safe handling information on this product, consult the Safety Data Sheet (SDS).

FIRST AID: In case of eye contact, flush immediately with water for 15 minutes and get medical help. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. If swallowed, drink large quantities of water. DO NOT induce vomiting. GET PHYSICIAN ASSISTANCE IN ALL CASES. Cured foam is not harmful to health.

CONTAINS: Polymethylenepolyphenylisocyanate, Dimethylether, Isobutane and Propane

STORAGE AND SHELF LIFE

When stored upright in a dry environment at or below 70°F (21°C), **BOSS® 336** has a shelf life of 12 months from date of shipment. In countries where high heat and humidity are a factor, special precautions must be taken. Store product in a covered, well-ventilated warehouse and avoid excessive heat conditions. Storage in high heat, high humidity conditions may reduce shelf life by up to 30%. Rotation of stock is an absolute necessity. Cartons should always be stacked upright with the cap pointed upwards. DO NOT stack cartons on their side. **NEVER** stack cartons more than 8 high. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building.

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

TECHNICAL DATA SHEET

COLORS

- Tan

PACKAGING

- 24 oz. can

Limited Warranty: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



Soudal Accumetric

MADE IN BELGIUM

350 Ring Road
Elizabethtown, KY 42701
800-928-BOSS(2677)
270-769-3385
FAX 270-765-2412
www.bossproducts.com

BOSS is a registered trademark of Soudal